


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 159.93 lm/W			
MODEL	240H5 110	Imax(cd)	15909	S/MH(C0/180)	1.55
NOMINAL POWER(W)	240	LOR(%)	100.0	S/MH(C90/270)	1.54
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	38384	η UP,DN(C0-180)	0.0,50.5
NOMINAL FLUX(lm)	38400	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.5
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	220.1	η down(%)	100.0	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017.7.13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1469	1461	1457	1453	1474	1458	1445	1439	0- 10	1389	1389	3.62,3.62
20	1456	1461	1471	1462	1477	1454	1439	1426	10- 20	4117	5506	14.3,14.3
30	1479	1514	1550	1541	1555	1517	1482	1452	20- 30	6821	12327	32.1,32.1
40	1495	1503	1497	1504	1522	1502	1468	1466	30- 40	9596	21923	57.1,57.1
50	1029	1014	1015	1011	1030	996.6	993.7	1003	40- 50	9979	31901	83.1,83.1
60	125.3	153.0	169.8	171.3	144.9	132.5	131.3	138.2	50- 60	5001	36903	96.1,96.1
70	48.41	61.45	56.57	59.84	55.06	56.07	50.94	57.43	60- 70	887.2	37790	98.5,98.4
80	21.97	27.72	29.19	28.47	22.20	27.94	28.03	27.13	70- 80	407.9	38198	99.5,99.5
90	3.117	8.810	11.22	10.37	3.456	10.43	11.40	10.25	80- 90	186.2	38384	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

Conical surface Flux(90deg): 27160 lm

%lum = 70.8%

%lamp = 70.7%

Conical surface Flux(120deg): 36903 lm

%lum = 96.1%


%lamp = 96.1%

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2017.7.13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	35972	68912
80	37651	50026
75	32524	43187
70	42125	49224
65	52615	66298
60	74557	101077
55	279023	309741
50	476507	469923
45	562534	553500

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017.7.13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.240	.136	.043	.233	.133	.042	.220	.126	.040	.208	.120	.038	.197	.114	.037		
2.0	.234	.128	.039	.228	.126	.039	.217	.121	.037	.207	.116	.036	.197	.112	.035		
3.0	.224	.119	.036	.219	.117	.035	.209	.113	.034	.200	.110	.034	.192	.106	.033		
4.0	.213	.111	.033	.209	.109	.032	.200	.106	.032	.192	.103	.031	.185	.100	.031		
5.0	.202	.103	.030	.198	.102	.030	.190	.099	.029	.183	.097	.029	.176	.094	.028		
6.0	.191	.096	.027	.188	.095	.027	.181	.093	.027	.174	.091	.027	.168	.089	.026		
7.0	.181	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.160	.083	.025		
8.0	.171	.084	.024	.169	.083	.023	.163	.081	.023	.158	.080	.023	.153	.078	.023		
9.0	.162	.079	.022	.160	.078	.022	.155	.077	.022	.150	.075	.022	.146	.074	.021		
10.0	.154	.074	.021	.152	.073	.020	.147	.072	.020	.143	.071	.020	.139	.070	.020		

ρcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.175	.157	.140	.150	.134	.120	.103	.093	.083	.059	.054	.048	.019	.017	.016		
2.0	.164	.132	.105	.141	.114	.091	.097	.079	.063	.056	.046	.037	.018	.015	.012		
3.0	.156	.114	.081	.133	.098	.070	.092	.068	.049	.053	.040	.029	.017	.013	.009		
4.0	.148	.100	.064	.127	.087	.055	.087	.060	.039	.051	.035	.023	.016	.012	.008		
5.0	.141	.089	.051	.121	.077	.045	.083	.054	.032	.048	.032	.019	.016	.010	.006		
6.0	.135	.081	.042	.116	.070	.037	.080	.049	.026	.046	.029	.016	.015	.009	.005		
7.0	.129	.074	.036	.111	.064	.031	.076	.045	.022	.044	.026	.013	.014	.009	.004		
8.0	.123	.068	.030	.106	.059	.027	.073	.042	.019	.043	.024	.011	.014	.008	.004		
9.0	.118	.063	.027	.101	.055	.023	.070	.039	.016	.041	.023	.010	.013	.007	.003		
10.0	.113	.059	.023	.097	.051	.020	.067	.036	.015	.039	.021	.009	.013	.007	.003		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017.7.13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

NAME: LED LIGHT					TYPE:					WEIGHT:				
SPEC.:					DIM.:					SERIAL No.:				
MFR.:					SUR.:21cm*16cm					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					19.9	21.2	20.1	21.4	21.6	19.9	21.3	20.2	21.5	21.6
3H					19.7	21.0	20.0	21.2	21.4	19.8	21.0	20.1	21.2	21.5
4H					19.7	20.8	20.0	21.1	21.3	19.7	20.9	20.0	21.1	21.4
6H					19.6	20.7	19.9	20.9	21.2	19.7	20.7	20.0	21.0	21.3
8H					19.5	20.6	19.9	20.9	21.1	19.6	20.7	20.0	20.9	21.2
12H					19.5	20.5	19.9	20.8	21.1	19.6	20.6	20.0	20.9	21.2
4H 2H					19.7	20.9	20.0	21.1	21.4	19.8	20.9	20.1	21.2	21.4
3H					19.6	20.6	20.0	20.9	21.2	19.7	20.7	20.0	21.0	21.2
4H					19.6	20.5	19.9	20.8	21.1	19.6	20.5	20.0	20.8	21.2
6H					19.5	20.3	19.9	20.7	21.0	19.6	20.4	20.0	20.7	21.1
8H					19.5	20.2	19.9	20.6	21.0	19.6	20.3	20.0	20.7	21.1
12H					19.5	20.1	19.9	20.5	20.9	19.6	20.3	20.0	20.6	21.0
8H 4H					19.5	20.2	19.9	20.6	20.9	19.5	20.3	19.9	20.6	21.0
6H					19.5	20.1	19.9	20.5	20.9	19.5	20.1	20.0	20.5	20.9
8H					19.5	20.0	19.9	20.4	20.9	19.5	20.1	20.0	20.5	20.9
12H					19.5	19.9	19.9	20.4	20.8	19.6	20.0	20.1	20.5	20.9
12H 4H					19.4	20.1	19.9	20.5	20.9	19.5	20.2	19.9	20.5	20.9
6H					19.4	20.0	19.9	20.4	20.8	19.5	20.0	20.0	20.4	20.9
8H					19.5	19.9	19.9	20.3	20.8	19.5	20.0	20.0	20.4	20.9
Variations with the observer position at spacings:														
S = 1.0H					+ 1.8 / - 2.9					+ 1.6 / - 2.3				
1.5H					+ 0.9 / - 1.6					+ 0.8 / - 1.5				
2.0H					+ 3.6 / - 7.1					+ 3.4 / - 6.7				

CIE Pub.117, 38400 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 12.7)

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017.7.13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	64	53	47	63	53	47	62	52	47	41
0.80	75	65	58	74	64	58	72	64	58	52
1.00	84	75	69	83	74	68	81	75	68	62
1.25	91	83	77	90	82	76	87	81	76	70
1.50	95	88	82	94	87	82	91	85	81	74
2.00	101	95	90	100	94	89	96	91	88	81
2.50	104	98	93	102	97	92	99	94	91	83
3.00	107	101	97	105	100	96	101	97	94	86
4.00	109	105	101	107	103	100	103	100	97	89
5.00	111	107	104	109	105	102	104	102	99	91
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004										
Suspended										
SHRNOM = 1.25										

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017.7.13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017.7.13

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

AAI Figure

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

Flux out:34812 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2017.7.13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2017.7.13

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

