


## LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 165.06 lm/W
MODEL	240H4 110	Imax(cd)	16420	S/MH(C0/180)	1.55	
NOMINAL POWER(W)	240	LOR(%)	100.0	S/MH(C90/270)	1.54	
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	39615	$\eta$ UP,DN(C0-180)	0.0,50.5	
NOMINAL FLUX(lm)	39600	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,49.5	
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.50	
TEST VOLTAGE(V)	220.1	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.55	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	1516	1508	1504	1499	1521	1505	1492	1486	0- 10	1433	1433	3.62,3.62
20	1503	1508	1518	1509	1524	1501	1485	1472	10- 20	4249	5682	14.3,14.3
30	1527	1562	1600	1590	1604	1566	1530	1499	20- 30	7040	12722	32.1,32.1
40	1543	1551	1545	1553	1570	1550	1515	1513	30- 40	9904	22626	57.1,57.1
50	1062	1046	1047	1044	1063	1029	1026	1035	40- 50	10299	32925	83.1,83.1
60	129.3	157.9	175.3	176.8	149.5	136.8	135.5	142.6	50- 60	5162	38087	96.1,96.2
70	49.96	63.42	58.38	61.76	56.82	57.87	52.57	59.28	60- 70	915.7	39002	98.5,98.5
80	22.67	28.61	30.12	29.39	22.92	28.84	28.93	28.00	70- 80	421.0	39423	99.5,99.6
90	3.217	9.093	11.58	10.70	3.567	10.76	11.77	10.58	80- 90	192.2	39615	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

Conical surface Flux(90deg): 28032 lm

%lum = 70.8%

%lamp = 70.8%

Conical surface Flux(120deg): 38087 lm

%lum = 96.1%


%lamp = 96.2%

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	37126	71123
80	38859	51631
75	33567	44573
70	43476	50804
65	54303	68425
60	76950	104320
55	287976	319678
50	491796	485001
45	580582	571259

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## WEC AND CCEC

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.240	.136	.043	.233	.133	.042	.220	.126	.040	.208	.120	.039	.197	.114	.037		
2.0	.234	.128	.039	.228	.126	.039	.217	.121	.038	.207	.116	.036	.197	.112	.035		
3.0	.224	.119	.036	.219	.117	.035	.209	.114	.035	.200	.110	.034	.192	.106	.033		
4.0	.213	.111	.033	.209	.109	.032	.200	.106	.032	.192	.103	.031	.185	.100	.031		
5.0	.202	.103	.030	.198	.102	.030	.190	.099	.029	.183	.097	.029	.177	.094	.028		
6.0	.191	.096	.027	.188	.095	.027	.181	.093	.027	.175	.091	.027	.169	.089	.026		
7.0	.181	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.161	.083	.025		
8.0	.172	.084	.024	.169	.083	.023	.163	.081	.023	.158	.080	.023	.153	.079	.023		
9.0	.163	.079	.022	.160	.078	.022	.155	.077	.022	.150	.075	.022	.146	.074	.021		
10.0	.154	.074	.021	.152	.073	.020	.147	.072	.020	.143	.071	.020	.139	.070	.020		

ρcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.191	.191	.191	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.176	.157	.140	.150	.135	.120	.103	.093	.083	.059	.054	.048	.019	.017	.016		
2.0	.165	.132	.105	.141	.114	.091	.097	.079	.063	.056	.046	.037	.018	.015	.012		
3.0	.156	.114	.081	.134	.098	.070	.092	.068	.049	.053	.040	.029	.017	.013	.009		
4.0	.148	.100	.064	.127	.087	.055	.087	.060	.039	.051	.035	.023	.016	.012	.008		
5.0	.141	.089	.051	.121	.077	.045	.084	.054	.032	.048	.032	.019	.016	.010	.006		
6.0	.135	.081	.042	.116	.070	.037	.080	.049	.026	.046	.029	.016	.015	.009	.005		
7.0	.129	.074	.036	.111	.064	.031	.077	.045	.022	.044	.026	.013	.014	.009	.004		
8.0	.123	.068	.031	.106	.059	.027	.073	.042	.019	.043	.025	.011	.014	.008	.004		
9.0	.118	.063	.027	.102	.055	.023	.070	.039	.016	.041	.023	.010	.013	.007	.003		
10.0	.113	.059	.023	.097	.051	.020	.067	.036	.015	.039	.021	.009	.013	.007	.003		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

NAME: LED LIGHT					TYPE:					WEIGHT:				
SPEC.:					DIM.:					SERIAL No.:				
MFR.:					SUR.:21cm*16cm					Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					19.9	21.2	20.1	21.4	21.6	19.9	21.3	20.2	21.5	21.6
3H					19.7	21.0	20.0	21.2	21.4	19.8	21.0	20.1	21.2	21.5
4H					19.7	20.8	20.0	21.1	21.3	19.7	20.9	20.0	21.1	21.4
6H					19.6	20.7	19.9	20.9	21.2	19.7	20.7	20.0	21.0	21.3
8H					19.6	20.6	19.9	20.9	21.1	19.6	20.7	20.0	21.0	21.2
12H					19.5	20.5	19.9	20.8	21.1	19.6	20.6	20.0	20.9	21.2
4H 2H					19.7	20.9	20.0	21.1	21.4	19.8	20.9	20.1	21.2	21.4
3H					19.6	20.6	20.0	20.9	21.2	19.7	20.7	20.0	21.0	21.2
4H					19.6	20.5	19.9	20.8	21.1	19.6	20.5	20.0	20.8	21.2
6H					19.5	20.3	19.9	20.7	21.0	19.6	20.4	20.0	20.7	21.1
8H					19.5	20.2	19.9	20.6	21.0	19.6	20.3	20.0	20.7	21.1
12H					19.5	20.1	19.9	20.5	20.9	19.6	20.3	20.0	20.6	21.0
8H 4H					19.5	20.2	19.9	20.6	20.9	19.5	20.3	19.9	20.6	21.0
6H					19.5	20.1	19.9	20.5	20.9	19.5	20.1	20.0	20.5	20.9
8H					19.5	20.0	19.9	20.4	20.9	19.5	20.1	20.0	20.5	20.9
12H					19.5	19.9	19.9	20.4	20.8	19.6	20.0	20.1	20.5	20.9
12H 4H					19.4	20.1	19.9	20.5	20.9	19.5	20.2	19.9	20.5	20.9
6H					19.4	20.0	19.9	20.4	20.8	19.5	20.0	20.0	20.4	20.9
8H					19.5	19.9	19.9	20.3	20.8	19.5	20.0	20.0	20.4	20.9
Variations with the observer position at spacings:														
S = 1.0H					+ 1.8 / - 2.9					+ 1.6 / - 2.3				
1.5H					+ 0.9 / - 1.6					+ 0.8 / - 1.5				
2.0H					+ 3.6 / - 7.1					+ 3.4 / - 6.7				

CIE Pub.117, 39600 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 12.8)

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	64	53	47	63	53	47	62	52	47	41
0.80	75	65	58	74	64	58	72	64	58	52
1.00	84	75	69	83	74	68	81	75	68	62
1.25	91	83	77	90	82	76	87	81	76	70
1.50	96	88	82	94	87	82	91	85	81	74
2.00	101	95	90	100	94	89	97	92	88	81
2.50	104	98	93	102	97	93	99	94	91	83
3.00	107	101	97	105	100	96	101	97	94	86
4.00	109	105	101	107	103	100	103	100	97	89
5.00	111	107	104	109	105	102	104	102	99	91
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004										
Suspended										
SHRNOM = 1.25										

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

ISOCANDELA DIAGRAM

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

AAI Figure

NAME: LED LIGHT	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017.7.13

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:



## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2017.7.13

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:



