



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 165.00 lm/W			
MODEL	ZGSM-SDD160H4	I <sub>max</sub> (cd)	10944	η street_up(%)	0.0
NOMINAL POWER(W)	160	LOR(%)	100.0	η street_down(%)	50.5
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	26400	η house_up(%)	0.0
NOMINAL FLUX(lm)	26400	MAXIMUM @(C,γ )	180,35.0	η house_down(%)	49.5
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	20.338




C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:



Classification:



IES:Type V - Very Short  
 CIE:Narrow - Short  
 IES:Full cut-off  
 CIE:Full cut-off  
 Max.At80:8.042cd/klm  
 Max.At90:0cd/klm  
 Max.80-90:8.042cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	10944
90%	9849
80%	8755
70%	7661
60%	6566
50%	5472
40%	4377
30%	3283
20%	2189
10%	1094
5%	547

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

# COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	lum,lamp
10	1010	1005	1002	999.3	1014	1003	994.2	990.1	0- 10	955.3	955.3	3.62,3.62
20	1002	1005	1012	1006	1016	1000	989.8	981.1	10- 20	2832	3787	14.3,14.3
30	1017	1041	1066	1060	1069	1043	1020	999.0	20- 30	4692	8479	32.1,32.1
40	1028	1034	1030	1035	1047	1033	1010	1008	30- 40	6601	15080	57.1,57.1
50	707.9	697.2	698.1	695.7	708.7	685.6	683.5	690.2	40- 50	6864	21944	83.1,83.1
60	86.16	105.2	116.8	117.8	99.66	91.15	90.32	95.04	50- 60	3440	25384	96.2,96.2
70	33.30	42.27	38.91	41.16	37.87	38.57	35.04	39.51	60- 70	610.3	25995	98.5,98.5
80	15.11	19.07	20.08	19.59	15.27	19.22	19.28	18.66	70- 80	280.6	26275	99.5,99.5
90	0	0	0	0	0	0	0	0	80- 90	124.7	26400	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

**ISOCANDELA DIAGRAM**


NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve




C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity: 65.0%  
 Test Distance: 10.480m [K=1.0000]  
 Remarks:

### LCS REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:

### LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:

#### IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	4266.8	16.2
FM - Front-Medium(30-60)	8537.3	32.3
FH - Front-High(60-80)	463.38	1.8
FVH - Front-Very High(80-90)	62.611	0.2
Total Forward Light	13330	50.5

BL - Back-Low(0-30)	4212.6	16.0
BM - Back-Medium(30-60)	8367.7	31.7
BH - Back-High(60-80)	427.56	1.6
BVH - Back-Very High(80-90)	62.109	0.2
Total Back Light	13070	49.5

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B4-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	13070	0	13070
Street Side	13330	0	13330

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018


γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:



ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:5.2kg
SPEC.:	DIM.: 385*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*296 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```