



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 125.00 lm/W			
MODEL	ZGSM-SDD180H6	I <sub>max</sub> (cd)	8890	η street_up(%)	0.0
NOMINAL POWER(W)	180	LOR(%)	100.0	η street_down(%)	51.1
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	22500	η house_up(%)	0.0
NOMINAL FLUX(lm)	22500	MAXIMUM @(C,γ )	15,37.0	η house_down(%)	48.9
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	21.836




C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:



Classification:



IES:Type V - Very Short  
 CIE:Narrow - Short  
 IES:Full cut-off  
 CIE:Full cut-off  
 Max.At80:22.60cd/klm  
 Max.At90:0cd/klm  
 Max.80-90:22.60cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	8890
90%	8001
80%	7112
70%	6223
60%	5334
50%	4445
40%	3556
30%	2667
20%	1778
10%	889
5%	444

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

# COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	lum,lamp
10	7185	7206	7156	7039	6997	7034	7131	7167	0- 10	674.9	674.9	3,3
20	7588	7461	7300	7204	7189	7232	7367	7512	10- 20	2047	2722	12.1,12.1
30	8269	7957	7573	7439	7417	7541	7793	8267	20- 30	3492	6213	27.6,27.6
40	8744	8636	8224	7661	7533	7607	8042	8433	30- 40	5060	11273	50.1,50.1
50	6496	6701	6411	5624	5321	5370	5851	6123	40- 50	5640	16913	75.2,75.2
60	2507	2495	2010	1858	1809	1552	1513	1870	50- 60	3485	20398	90.7,90.7
70	1020	952.3	804.4	911.6	947.3	890.2	750.4	892.9	60- 70	1238	21636	96.2,96.2
80	410.9	467.9	344.0	410.8	361.6	362.9	64.23	395.8	70- 80	693.3	22329	99.2,99.2
90	0	0	0	0	0	0	0	0	80- 90	171.2	22500	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

# ISOCANDELA DIAGRAM


NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### Planar Illuminance Curve




C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: DAMIN  
 Test Date: 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity: 65.0%  
 Test Distance: 10.480m [K=1.0000]  
 Remarks:

### LCS REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

### LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

#### IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	3102.6	13.8
FM - Front-Medium(30-60)	7277.8	32.3
FH - Front-High(60-80)	1013.2	4.5
FVH - Front-Very High(80-90)	101.55	0.5
Total Forward Light	11495	51.1

BL - Back-Low(0-30)	3110.5	13.8
BM - Back-Medium(30-60)	6906.8	30.7
BH - Back-High(60-80)	918.25	4.1
BVH - Back-Very High(80-90)	69.663	0.3
Total Back Light	11005	48.9

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B4-U0-G2
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	11005	0	11005
Street Side	11495	0	11495

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018


γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:



ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 3030	WEIGHT:4.4kg
SPEC.:	DIM.: 312*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*222 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```