



STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 165.00 lm/W			
MODEL	ZGSM-SDD80H4	Imax(cd)	5472	η street_up(%)	0.0
NOMINAL POWER(W)	80	LOR(%)	100.0	η street_down(%)	50.5
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	13200	η house_up(%)	0.0
NOMINAL FLUX(lm)	13200	MAXIMUM @(C, γ)	180,35.0	η house_down(%)	49.5
LAMPS INSIDE	1	η up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	η down(%)	100.0	SLI	19.341




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:



Classification:



IES:Type V - Very Short
 CIE:Narrow - Short
 IES:Full cut-off
 CIE:Full cut-off
 Max.At80:8.042cd/klm
 Max.At90:0cd/klm
 Max.80-90:8.042cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	5472
90%	4925
80%	4377
70%	3830
60%	3283
50%	2736
40%	2189
30%	1642
20%	1094
10%	547
5%	274

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

COEFFICIENT OF UTILIZATION CURVE AND ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 γ Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	lum,lamp
10	5051	5025	5012	4996	5070	5014	4971	4951	0- 10	477.6	477.6	3.62,3.62
20	5009	5026	5059	5028	5079	5002	4949	4905	10- 20	1416	1894	14.3,14.3
30	5087	5206	5331	5300	5347	5217	5098	4995	20- 30	2346	4240	32.1,32.1
40	5142	5168	5148	5174	5233	5166	5050	5042	30- 40	3300	7540	57.1,57.1
50	3540	3486	3491	3479	3544	3428	3418	3451	40- 50	3432	10972	83.1,83.1
60	430.8	526.2	584.0	589.1	498.3	455.7	451.6	475.2	50- 60	1720	12692	96.2,96.2
70	166.5	211.3	194.6	205.8	189.4	192.8	175.2	197.5	60- 70	305.2	12997	98.5,98.5
80	75.55	95.33	100.4	97.93	76.37	96.10	96.41	93.29	70- 80	140.3	13137	99.5,99.5
90	0	0	0	0	0	0	0	0	80- 90	62.36	13200	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM


NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.480m [K=1.0000]
 Remarks:

LCS REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

BUG REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	2133.4	16.2
FM - Front-Medium(30-60)	4268.6	32.3
FH - Front-High(60-80)	231.69	1.8
FVH - Front-Very High(80-90)	31.305	0.2
Total Forward Light	6664.9	50.5

BL - Back-Low(0-30)	2106.3	16.0
BM - Back-Medium(30-60)	4183.8	31.7
BH - Back-High(60-80)	213.77	1.6
BVH - Back-Very High(80-90)	31.054	0.2
Total Back Light	6534.9	49.5

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B3-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	6534.9	0	6534.9
Street Side	6664.9	0	6664.9


C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED Tunnel Lights	TYPE:5S 5050	WEIGHT:3.5kg
SPEC.:	DIM.: 239*270*165mm	SERIAL No.:
MFR.: ZGSM	SUR.:250*144 mm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.480m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.480m [K=1.0000]
Remarks:

```